

Specification Guide

M Series A1 Refrigerants

Manufactured Housing Evaporator Coils

Features

- High efficiency lanced fin design.
- "No-hassle" 5-year warranty. 10 year Limited Warranty available.
- R-22, R-410A, AC & Heat Pump compatible.
- All coils have durable packaging with bar coded labels on the box.
- Threaded expansion valves available factory installed or as a field installed kit.
- Coils are air pressure tested at 500 psi, leak tested with helium, sealed with rubber plugs, then charged with dry air.
- Downflow drip shields are molded into drain pan.
- Filter-friendly top plate on most models (except 22" & above).
- Down-turned headers are sized out to easily receive line set.
- Factory software for TXV failure testing.
- Includes die-cut foam sheet for sealing, drain ELL, drain hose & clamp.
- Dedicated upflow/downflow.
- Copper refrigerant connections for easy brazing.
- Rifled copper tubing.



Available Options

- Field or factory installed threaded expansion valve.

Slab Number	Nominal Tonnage	Pan Width	Pan Depth	Coil Height	Weight	Pallet Qty
E22	1.5 - 3	18"	19 1/2"	15"	23	8
E23	1.5 - 3	18"	19 1/2"	17"	26	8
E24	1.5 - 3.5	18"	19 1/2"	19"	27	8
E30	1.5 - 2	18"	19 1/2"	11"	22	8
E31	1.5 - 2.5	18"	19 1/2"	13"	24	8
E32	1.5 - 3	18"	19 1/2"	15"	28	8
E33	1.5 - 3	18"	19 1/2"	17"	32	8
E34	3 - 5	18"	19 1/2"	19"	35	8
E35	3 - 5	18"	19 1/2"	21"	39	4
E36	3 - 5	18"	19 1/2"	23"	41	4
E49	3.5 - 5	18"	19 1/2"	25"	46	4
E58	2 - 3	18"	19 1/2"	17"	42	8
E59	3 - 5	18"	19 1/2"	19"	45	8
E66	3 - 5	18"	19 1/2"	21"	48	4
E67	4 - 5	18"	19 1/2"	23"	49	4



Product improvement is a continuous process at Advanced Distributor Products. Therefore, product specifications are subject to change without notice and without obligation on our part. Please contact your ADP representative or distributor to verify details.

© 2025 by Advanced Distributor Products. All rights reserved.

Product Nomenclature

M 24 E32 9

Series

M = Manufactured Housing
(Uncased)

Nominal MBTUH

Slab Number

E30
E31

Metering Device

- 1 = Piston (R-410A)*
- 7 = Bleed H/P TXV (R-410A)
- 9 = Non-Bleed H/P TXV (R-410A)

* Piston will always be sized to match the nominal BTU rating of the coil

Installed Piston Sizes	
MBTUH	R-410A
12	41
18	49
24	53
30	59
36	67
42	73
48	76
60	93

