

Specification Guide

M Series A2L Refrigerants

Manufactured Housing Evaporator Coils

Features

- High efficiency lanced fin design.
- “No-hassle” 5-year warranty. 10 year Limited Warranty available.
- R-32, R454B, AC & Heat Pump compatible with Refrigerant Detection System
- All coils have durable packaging with bar coded labels on the box.
- Threaded expansion valves available factory installed or as a field installed kit.
- Factory installed Refrigerant Detection Sensor Bracket
- Coils are air pressure tested at 500 psi, leak tested with helium, sealed with rubber plugs, then charged with dry air.
- Downflow drip shields are molded into drain pan.
- Filter-friendly top plate on most models (except 22" & above).
- Down-turned headers are sized out to easily receive line set.
- Factory software for TXV failure testing.
- Includes die-cut foam sheet for sealing, drain ELL, drain hose & clamp.
- Dedicated upflow/downflow.
- Copper refrigerant connections for easy brazing on both copper and aluminum slab models.
- Rifled copper tubing.
- Refrigerant Detection System Options:
 - Field Installed Sensor and board with factory installed bracket.
 - Factory installed sensor and mitigation board in box.
 - Factory installed sensor only without board for compatible furnaces.



Available Options

- Field or factory installed threaded expansion valve.


Slab Number	Nominal Tonnage	Pan Width	Pan Depth	Coil Height	Copper coil Weight	Aluminum coil Weight	Pallet Qty
(E,G) 22	1.5 - 3	18"	19 1/2"	15"	23	18	8
(E,G) 23	1.5 - 3	18"	19 1/2"	17"	26	21	8
(E,G) 24	1.5 - 3.5	18"	19 1/2"	19"	27	22	8
(E,G) 30	1.5 - 2	18"	19 1/2"	11"	22	18	8
(E,G) 31	1.5 - 2.5	18"	19 1/2"	13"	24	19	8
(E,G) 32	1.5 - 3	18"	19 1/2"	15"	28	22	8
(E,G) 33	1.5 - 3	18"	19 1/2"	17"	32	26	8
(E,G) 34	3 - 5	18"	19 1/2"	19"	35	28	8
(E,G) 35	3 - 5	18"	19 1/2"	21"	39	31	4
(E,G) 36	3 - 5	18"	19 1/2"	23"	41	33	4
(E,G) 49	3.5 - 5	18"	19 1/2"	25"	47	38	4
(E,G) 52	4 - 5	18"	19 1/2"	31"	62	50	4
(E,G) 55	3.5 - 5	18"	19 1/2"	31"	50	40	4
(E,G) 58	2 - 3	18"	19 1/2"	17"	42	32	8
(E,G) 59	3 - 5	18"	19 1/2"	19"	45	34	8
(E,G) 66	3 - 5	18"	19 1/2"	21"	48	35	4
(E,G) 67	4 - 5	18"	19 1/2"	23"	49	38	4



Product improvement is a continuous process at Advanced Distributor Products. Therefore, product specifications are subject to change without notice and without obligation on our part. Please contact your ADP representative or distributor to verify details.

© 2025 by Advanced Distributor Products. All rights reserved.

Product Nomenclature



* R-454B Piston factory installed
to match the nominal BTU rating of the coil.

R-454B Pistons	
MBTUH	Size
18	46
24	53
30	59
36	65
42	70
48	76
60	84

R-32 Pistons	
MBTUH	Size
18	41
24	46
30	53
36	57
42	62
48	65
60	76

